


Foam Wheeled Extinguisher 50 liters AB (cartridge)

Wheeled extinguisher is designed for professional use under severe circumstances, resulting in a high level of quality and ease of use. The cylinder, CE marked, has the welded frame. Ease of mobility is achieved as a result of the large wheels with solid rubber tyres and push bar also ensuring good stability during operation.



Applications for marine, inland shipping and offshore market

- engine rooms
- car decks
- heli decks

Features

- suitable placing of handle and 300 mm wheels + turning little wheel in order to guarantee and optimal stability and easiness of use, as well as a good mobility of the device
- diameter cylinder 315 +0 -15 mm, material AISI 304
- easy running diam. 300 wheels + additional turning wheel for an easy movement
- 5 meters length hose with foam making nozzle and ball valve for the best possible use and effectiveness on the fire by the operator
- 3/4 ball valve at the end of the hose for a dosed projection of the extinguishing agent
- on request available antifreeze -20°C or -30°C
- painted inside

TECHNICAL SPECIFICATIONS

Manufacturer / Model	14260 3
Extinguisher	AFFF foam
Capacity	50 liter
Fire class / Rating	A B
Propellant gas	CO ₂ , 1.3 kgs
Discharge time	47 seconds
Throw length	8 meters
Working pressure	14 bar at 20°C
Suitable for electrical equipment	Not tested
Extinguishing agent	AFFF foam
Length discharge hose	5 meters
Diameter wheels	300 mm
Material wheels	Hard rubber / PVC
Temperature range	+0°C to +60°C
Approx gross weight	50 liter
Approx dispatch weight	85.0 kgs
Approx unit dimension	550 x 455 x 1145 mm (l x w x h)
Color	Cylinder red RAL 3000
Approvals	EN 1866 / CE, MED