

## Emergency Tank Shower

Emergency Tank Shower incorporating a 1.200 litre tank with galvanised mild steel rectangular hollow section frame and White GRP outer casing.



### General information

An integral immersion heater, controlled by a dual safety thermostat, maintains the water in the insulated tank at a constant temperature to deliver a guaranteed flow of warm water for up to 15 minutes even when the mains supply has been disrupted.

The shower is activated when the casualty stands on the optional Foot Panel or pushes the panic bar. A version is available with the Eye/Facewash Fountain mounted internally. Alternatively the Eye/Facewash can be omitted.

Also available with GRP casing in Green. Also available with stainless steel frame.

Export Model EXP-MH-14K/1200. Insulated models available, without heating STD-J-14K/1200, EXP-J-14K/1200.

Note: An Earthquake proof version of this model is available which has been designed to conform to the California Building Code 1998 Chapter 16, Division 1.

### TECHNICAL SPECIFICATIONS

Manufacturer / Model	STD-MH-14K/1200
Dimensions	3666 (H) x 1310 (W) x 1310 (D)
Tank size	1.200 litre
Weight	300 kgs, approx. dry weight
Water inlet	2" flange
Water pressure	2 bar G
Heating	optional to specs
Cooling	optional to specs



**Emergency Tank Shower**  
1.200 litre tank