



Dräger PEX 3000

Detection of flammable gases and vapours

The Dräger PEX 3000 transmitter detects flammable gases and vapours in concentrations below their lower explosive limit (100 % LEL). It helps you to increase the explosion protection of your plant. Its heat-tone sensor reacts to gas within just a few seconds, and the measurement signal remains particularly stable over the long term.

Benefits

Two transmitter variants

Choose between two measurement ranges (0 to 100% or 0 to 10% LEL). Do you want to position the transmitter and sensor separately? The remote variant includes a second cable input instead of the built-in sensor for connecting a Polytron SE Ex remote measuring head.

Simple installation

The three stripped individual wires of the shielded measuring cable are simply inserted into the spring-loaded clamps provided on the transmitter. The sensor is connected in the same way. This type of contact is state of the art. It is more reliable than screw clamp technology, as it is impossible for it to loosen itself.

One-person calibration

You do not need an additional handheld control unit. Maintenance and calibration are carried out directly on the opened transmitter using only two buttons and a two-digit 7-segment display. And this is expressly permitted even in Ex areas!

Explosion protection

The Dräger PEX 3000 is approved according to the EU Directive 2014/34/EU for operating temperatures between -40 and +65 °C, making it suitable for use in both gas and dust hazardous Ex areas (Zones 1, 2, 21, and 22).

Low gas concentrations

The Dräger PEX 3000 Type XTR 0011 transmitter features a special low-drift LC sensor, making it ideal for detecting gases at low concentrations. It reliably detects gas leaks at levels below just 10% LEL.

The heat-tone sensor

The catalytic DrägerSensor... DQ is based on the heat-tone principle. The most important component is the hot, catalytically active beads on platinum coils (pellistors). These pellistors burn the gas, generating additional reaction heat. The temperature increases depending on the gas concentration, which in turn changes the electrical resistance of the platinum coils. This change is transmitted as a measurement signal. The double-detector compensation method ensures the heat-tone sensor remains particularly stable over the long term. The wire mesh at the gas inlet acts as a flame arrester. This provides explosion protection while maintaining a short response time.

System Components

D-10088-2018



Catalytic Bead DrägerSensor

The DrägerSensor ... DQ detects flammable gases and vapours such as hydrogen. Due to the double-detector compensation method, the catalytic sensor is particularly long-term stable. The wire mesh at the gas inlet serves as a flame barrier. So it ensures explosion protection at the same time short response time.

D-6806-2016



Dräger REGARD 7000

The Dräger REGARD 7000 is a modular and therefore highly expandable control system for monitoring various gases and vapours. Suitable for gas warning systems with various levels of complexity and numbers of transmitters, the Dräger REGARD 7000 also features exceptional reliability and efficiency. An additional benefit is the backward compatibility with the REGARD.

Related Products

D-6031-2025



Dräger Polytron SE Ex

The Dräger Polytron SE Ex ... DQ sensing heads are gas detectors for the continuous monitoring of flammable gases and vapours in the ambient air. Measurement is based on the heat of reaction principle where a chemical reaction takes place in a catalytic bead (also known as a pellistor) inside the sensor.

D-15005-2010_5DA_LC



Dräger Polytron 5200 CAT

The Dräger Polytron 5200 CAT is a cost-effective, explosion-proof transmitter designed for detecting flammable gases and vapours. It uses the catalytic DrägerSensor Ex... DQ. Due to the 3-wire operation and the 4 to 20 mA analogue output, you can combine the transmitter with most evaluation systems in your gas detection system.

D-797-2016



Dräger Polytron 8200 CAT

The Dräger Polytron 8200 CAT is an explosion-proof high-end transmitter designed for detecting flammable gases and vapours. It uses the catalytic DrägerSensor Ex... DQ. In addition to the 3-wire operation with a 4 to 20 mA analogue output, it also offers HART, fieldbus options and Modbus, allowing you to integrate the transmitter with most control systems in your gas detection system.

Technical Data

Dräger PEX 3000

Gases and vapours	Flammable gases and vapours in the ambient air, such as: Acetone, Acetylene, Ammonia, Petrol 065/095, Benzene, 1,3-Butadiene, n-Butane, n-Butyl acetate, Diethyl ether, Dimethyl ether, Ethanol, Ethyl acetate, Ethylene, Ethylene oxide, n-Hexane, Methane, Methanol, Methyl ethyl ketone (MEK), Methyl methacrylate, n-Nonane, n-Octane, n-Pentane, Propane, i-Propanol, Propylene, Propylene oxide, Toluene, Hydrogen, and o-Xylene, 1-Ethoxy-2-propanol, 1-Methoxy-2-propanol, Allyl alcohol, Ethane, i-Butane, i-Butene, Carbon monoxide, Methyl tert-butyl ether, N-Methyl-2-pyrrolidone, n-Propanol, Styrene	
Measuring range	Type XTR 0001	0 to 99% LEL
	Type XTR 0011	0 to 9.9% LEL
	Type XTR 0091 with measuring head SE Ex PR / HT ... DQ	0 to 99% LEL
	Type XTR 0091 with measuring head SE Ex LC ... DQ	0 to 9.9% LEL

Electrical data

Supply voltage	12 to 30 V DC (nominally 24 V DC), max. 110 mA at 24 V	
Maximum cable length (at 24 V, 250 Ohm)	2,400 m with 3 x 1.5 mm ² , 1,600 m with 3 x 1.0 mm ² , 1,200 m with 3 x 0.75 mm ²	
Output signals	Measuring mode	4 to 20 mA
	Maintenance	3.4 mA
	Fault	< 1.2 mA
Measurement setting time (at 25 °C, Methane)	Type XTR 0001	t ₅₀ : 3 ... 5 s
		t ₉₀ : 8 ... 10 s
	Type XTR 0011	t ₅₀ : < 9 s
		t ₉₀ : < 20 s

Housing

Housing material	Glass fibre reinforced polyester (GRP) with a metallic inner coating	
Housing protective rating	IP 66	
Dimensions (W x H x D)	Type XTR 00x1	approx. 110 x 145 x 55 mm
Weight	approx. 600 g (type XTR 0091: approx. 450 g)	
Sensor lifespan	Over 3 years on average	

Ambient conditions

Temperature	-40 to +65 °C (see below)	
Pressure	700 to 1,300 hPa	
Humidity	5 to 95 % RH	

Technical Data

Approvals

Device marking according to 2014/34/EU	Type XTR 0001 or XTR 0011	II 2G Ex db eb IIC T6/T5/T4 Gb
		II 2D Ex tb IIIC T80/95/130 °C Db IP6X -40 °C ≤ Ta ≤ +40/55/65 °C
	Type XTR 0091	II 2G Ex db eb IIC T6 Gb
		II 2D Ex tb IIIC T80 °C Db IP6X -40 °C ≤ Ta ≤ +65 °C
Suitability test	according to EN 60079-29-1 for the gases and vapours listed above (only 100 % LEL variants)	
Functional safety (only 100 % LEL variants)	Average probability of failure on demand (TP = 1 year)	PFD = 5.56E-04
	Proportion of safe failures (HFT = 0, Type B)	SFF = 90.4 %

Ordering Information

Dräger PEX 3000

Dräger PEX 3000, Type XTR 0001, medium-sized housing, 0 ... 100% LEL	8318360
Dräger PEX 3000, Type XTR 0011, medium-sized housing, 0 ... 10% LEL	8318370
Dräger PEX 3000, Type XTR 0091, medium-sized housing, remote transmitter without sensor	8318390
Dust filter for DrägerSensor PR M DQ (PE discs, pack of 10)	6810537
Calibration adapter (PE)	6806978
Process adapter (stainless steel) for Dräger PEX 3000 XTR 0001	6812470
Process adapter (stainless steel) for Dräger PEX 3000 XTR 0011	6812465
DrägerSensor PR M DQ	6814140

Not all products, features, or services are for sale in all countries. Trademarks mentioned herein are the property of its respective owner. Trademarks may be owned by Drägerwerk AG & Co. KGaA (Dräger) or its affiliates in certain countries and not necessarily in the country in which this material is released. Visit www.draeger.com/trademarks for the current status of Dräger's trademarks.

Corporate Headquarters

Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany
■ www.draeger.com

Region Europe

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
☎ +49 451 882 0
☎ +49 451 882 2080
✉ info@draeger.com

Region Asia Pacific

Draeger Singapore Pte. Ltd.
61 Science Park Road
The Galen #04-01
Singapore 117525
☎ +65 6872 9288
☎ +65 6259 0398

Region Middle East, Africa

Dräger Safety AG & Co. KGaA
Branch Office
P.O. Box 505108
Dubai, United Arab Emirates
☎ +971 4 4294 600
☎ +971 4 4294 699
✉ contactuae@draeger.com

Region Central and South America

Dräger Safety do Brasil Ltda.
Al. Pucuruí, 51/61 – Tamboré
06460-100 Barueri, São Paulo
☎ +55 (11) 4689-4900
✉ relacionamento@draeger.com



Locate your Regional Sales
Representative at:
www.draeger.com/contact