

POK Portable Oscillating Monitor

500 GPM Blitz Fire Attack Monitor. Quick locking ladder attachments are options.



Features

- 500 GDM Blitz Fir Attack monitor
- only one with full 360° rotation
- only one -20° to 80° vertical travel with built in stop at 30°
- storage size of only 19"L x 7"W x 8"H
- 0° to 60° automatic oscillating and quick locking ladder attachments are options

Vertical elevation control and safety stop release

When mounted on a ladder attachment, the nozzle may be lowered below the 30° stop. When the nozzle is raised back above 30°, the spring loaded stop release will snap back into position automatically, limiting the elevation of the nozzle with respect to the base at 30°.

Portable base

The portable base allows the monitor to be positioned in places that are not accessible with a fire truck. The legs are made of titanium and will flex when in use to compensate for small ground irregularities. It is intended for a maximum flow of 2000 liters per minute.

Site selection

Safety operation of the monitor on the portable base begins with site selection. The site should be a safe distance from the fire yet within the reach of the nozzle stream. Select a flat even surface within 8 feet of a sturdy stationary object that can be used as an attachment point for the anchor strap. Set up the portable base with the anchor point between the portable base and desired target of the nozzle stream.

Maintenance

A positive advantage of the POK monitor is they require very little maintenance. However, in order to maintain optimal functioning of these monitors we advise you to apply grease to the greaser(s) frequently with the genuine POK grease. You will find several greasers on your monitor.

TECHNICAL SPECIFICATIONS

Flow	500 GPM at 100 PSI - 2000 l/mn at 7 bars
Weight	12 kg
Vertical range	80°
Material	Aluminum
Leg	Fold away titanium leg with carbide tips



POK Oscillating Monitor
Extremely compact and full 360°