



# Dräger X-am 5600 Multi-Gas Detector

---

Featuring an ergonomic design and innovative infrared sensor technology, the Dräger X-am 5600 is one of the smallest gas detection instrument for the measurement of up to 6 gases. Ideal for personal monitoring applications, this robust and water-tight detector provides accurate, reliable measurements of flammable and toxic gases and vapors as well as oxygen.

# Dräger X-am 5600

**Safe gas entry**  
Gas entry from two sides

**Visual alarm**  
360° visible alarm

**Crocodile clip**  
Secure attachment

**DrägerSensors**  
Quick, precise, long service life

**Robust design**  
Water and dust resistant  
in acc. with IP 67

**Large display**  
All values at a glance

D-23637-2009



# Benefits

## Small yet robust

Small, light and easy to use – the robust and water-tight gas detector X-am 5600 is designed for single-handed operation in tough industrial environments. Water- and dustproof according to IP 67 and with an integrated rubber boot, the device provides optimal functionality even under harsh conditions.

## Durable infrared technology

Thanks to the high stability and a resistance to contamination, Dräger infrared sensors can generally be used for up to eight years. This advanced technology reduces the cost of ownership considerably because less replacement sensors are needed. In addition, a calibration of the IR sensor is only necessary every 12 months which reduces maintenance costs.

## Single or dual sensor – accurate measurement results

The infrared sensor IR Ex allows the measurement of flammable hydrocarbons in the range of the lower explosive limit. The infrared sensor IR CO<sub>2</sub>, with a measurement resolution of 0.01 Vol.-%, provides safe and exact measurements as well as a warning against toxic concentrations of carbon dioxide in the ambient air. For those applications where the reliable measurement of flammable substances and CO<sub>2</sub> is specifically needed, the advantages of both can be achieved by a dual sensor (Dual IR CO<sub>2</sub>/Ex).

## Also in combination with Hydrogen

Besides hydrocarbons, hydrogen can also be a flammable gas. Because sensors based on infrared technology do not warn against hydrogen explosion dangers, the gas detector X-am 5600 combines two sensor signals (Infrared Ex and electrochemical H<sub>2</sub>HC) for reliable hydrogen detection. The X-am 5600 provides the advantages of poison-free technology to be used in areas where, until now, only catalytic Ex sensors have been used.

## Various monitoring possibilities

Thanks to the combination of innovative infrared technology and the latest electrochemical Dräger XXS miniature sensors, this 1-to-6 gas detector reliably detects flammable and harmful concentrations of O<sub>2</sub>, Cl<sub>2</sub>, CO, CO<sub>2</sub>, H<sub>2</sub>, H<sub>2</sub>S, HCN, NH<sub>3</sub>, NO, NO<sub>2</sub>, PH<sub>3</sub>, SO<sub>2</sub>, O<sub>3</sub>, Amine, Odorant, COCl<sub>2</sub> and organic vapors. With the PC software Dräger CC-Vision, the sensors can easily be exchanged, calibrated or converted to meet the needs of different applications.

## Flexible use

An optional external pump which can be operated with hoses up to 45 m in length is the perfect solution for pre-entry measurements in tanks or pipelines. To monitor entire areas, the gas detector X-am 5600 can be used in combination with the highly visible area monitor Dräger X-zone 5500/5800.

# Benefits


## Suitable for Ex-Zone 0

The small and reliable gas detector is suitable for use in areas classified as zone 0, which are areas where explosive atmospheres are always to be expected – also with Dräger X-am Pump and Dräger X-zone 5500/5800.

## Area monitoring

In combination with the Dräger X-zone 5500/5800 the gas detector can be used for various area monitoring applications. Up to 25 Dräger X-zone 5500/5800 units can be automatically interconnected to form a wireless fence. This interconnection of the area monitoring devices allows for the fast securing of larger areas, e.g. pipelines or industrial tanks – even within the scope of industrial shutdowns.


# System Components



D-12191-2010

## DrägerSensor XXS

Dräger has developed miniature electrochemical sensors specially for the Dräger Pac, X-am 1/2/5 and X-am 8000 generation. The sensors detect many different gases and vapours. They are also very reliable and stable over the long-term, thereby reducing your operating costs.



D-6151-2025

## Dräger Infrared Sensors

Dräger infrared sensors deliver optimal measurement results and are unaffected by sensor poisons. The long service life of these sensors results in hardly any follow-up costs. You can also use Dräger infrared sensors to take Ex and CO<sub>2</sub> measurements simultaneously.

# System Components

D-47907-2012



## Dräger X-dock 5300/6300/6600

The Dräger X-dock series provides you with full control of your portable Dräger gas detection instruments. Automatic bump tests and calibrations with reduced test gas consumption and short testing times save time and money. Comprehensive documentation and evaluations provide you with a clear overview.


D-24997-2020



## Dräger Bump Test Station

Easy function testing on site

D-40484-2021



## Gas Detection Connect

Dräger Gas Detection Connect is your connection to the digital future of occupational safety. The system connects individual Dräger products through a smart software solution. Thanks to location- and time-independent access, you manage your equipment optimally and always have the position and status of your gas detection equipment and workers available. So you can protect your workforce and increase the efficiency of your plant at the same time.

# Accessories

D-0494-2018



## Calibration gas and accessories

Calibration of equipment will ensure safe operation and functionality of equipment and will also meet with the applicable regulations and codes of practice. Various calibration gas options are easily available.

D-30746-2015



## Dräger Configuration and Evaluation Software

Save measurement results, professionally configure gas detection instruments and viewing performance data – all that is possible with the tailor-made Dräger software.

D-11857-2016



## Dräger X-am Pump

The Dräger X-am Pump is an external pump for the portable gas detectors Dräger X-am 2500/2800 and X-am 5000/5600/5800 – designed for clearance measurement, for example in tanks and shafts. The pump automatically switches on when it is connected to a running X-am device. The change from pump mode to diffusion mode is fast and easy.

D-12284-2009



## Power pack & Charging set

Consisting of: NiMH power supply, charging module, single charger

# Related Products

D-14325-2017



## Dräger X-am 5000

The Dräger X-am 5000 belongs to a generation of gas detectors, developed especially for personal monitoring applications. This 1- to 5-gas detector reliably measures combustible gases and vapors as well as oxygen and harmful concentrations of toxic gases, organic vapors, Odorant and Amine.

# Technical Data

Dimensions (W x H x D)	48 x 130 x 44 mm		
Weight	220 – 250 g		
Ambient conditions	Temperature	-20 to +50 °C -40 °C possible over a short period (ATEX & IECEx only), max. 15 minutes with NiMH supply unit T4 (HBT 0000) or T4 HC (HBT 0100), prerequisite: storage of the device at room temperature at room temperature (+20 °C) for at least 60 minutes.	
	Pressure	700 to 1,300 mbar	
	Relative humidity	10 to 95 % r.h.	
Protection class	IP 67		
Alarms	Visual	360°	
	Audible	Multi-tone > 90 dB at 30 cm	
	Vibration		
Operating times	~ 12 h >250 h without Ex Sensor		
Charging time	< 4 h		
Datalogger	Application of an optimized data compression method with high accuracy and large storage capacity (typically data compression >90% compared to the traditional data logger concept with adjustable interval)		
Pump operation	Maximum hose length 45 m; 148 ft.		
Approvals	ATEX	II 1G Ex da ia IIC T4/T3 Ga, I M1 Ex da ia I Ma	
	IECEX	Ex da ia IIC T4/T3 Ga, Ex da ia I Ma	
	CSA (Canada & USA)	Class I Div. 1 Groups A, B, C, D, E, F, G T4/T3 A/Ex ia IIC T4/T3 Ga	
	Measurement performance certificate	EN 50104	O <sub>2</sub>
		EN 45544-1, EN 45544-2, EN 45544-3	CO, H <sub>2</sub> S, CO <sub>2</sub> -Dual IR
		EN 60079-29-1	Methane to nonane, XXS H <sub>2</sub> HC
	CE mark	Electromagnetic Compatibility (Directive 2014/30/EU) ATEX (Directive 2014/34/EU)	
MED	Marine Equipment Directive (Directive 2014/90/EU)		
MER	Merchant Shipping (Marine Equipment) Regulations 2016		
EAC	PO Ex ia I Ma X		
	0Ex ia IIC T4/T3 Ga X		

# Ordering Information

## Dräger X-am 5600

Consisting of: basic instrument with an integrated data logger.  
A functional instrument must include up to 4 sensors and a power supply unit (option).

## 8321050

Infrared sensors	Measuring range	Resolution	Order code
Dual IR Ex/CO <sub>2</sub> ES <sup>1</sup>	0 - 100 % LEL 0 - 100 Vol.-% Methane, Propane, Ethene, n-Butane 0 - 5 Vol.-% CO <sub>2</sub>	1 % LEL 0.1 Vol.-% CH <sub>4</sub> 0.01 Vol.-% CO <sub>2</sub>	6851880
IR Ex ES <sup>1</sup>	0 - 100 % LEL 0 - 100 Vol.-% Methane, Propane, Ethene, n-Butane	1 % LEL 0.1 Vol.-% CH <sub>4</sub>	6851881
IR CO <sub>2</sub> ES	0 - 5 Vol.-% CO <sub>2</sub>	0.01 Vol.-% CO <sub>2</sub>	6851882
Electrochemical sensors	Measuring range	Resolution	Order code
XXS O <sub>2</sub> <sup>2</sup>	0 - 25 Vol.-%	0.1 Vol.-%	6810881
XXS CO LC	0 - 2,000 ppm	1 ppm	6813210
XXS O <sub>2</sub> 100	0 - 100 Vol.-%	0.5 Vol.-%	6812385
XXS O <sub>2</sub> PR	0 - 30 Vol.-%	0.1 Vol.-%	6800530
XXS CO HC	0 - 10,000 ppm	5 ppm	6812010
XXS CO/H <sub>2</sub> compensated	0 - 2,000 ppm CO	2 ppm	6811950
XXS H <sub>2</sub> S LC <sup>2</sup>	0 - 200 ppm	0.1 ppm	6811525
XXS H <sub>2</sub> S HC	0 - 1,000 ppm	2 ppm	6812015
XXS CO LC/H <sub>2</sub> S LC	0 - 2,000 ppm CO 0 - 100 ppm H <sub>2</sub> S	1 ppm CO 0.1 ppm H <sub>2</sub> S	6813280
XXS CO LC/O <sub>2</sub>	0 - 2,000 ppm CO 0 - 25 Vol.-% O <sub>2</sub>	1 ppm CO 0.1 Vol.-% O <sub>2</sub>	6813275
XXS H <sub>2</sub> S LC/O <sub>2</sub>	0 - 100 ppm H <sub>2</sub> S 0 - 25 Vol.-% O <sub>2</sub>	0.1 ppm H <sub>2</sub> S 0.1 Vol.-% O <sub>2</sub>	6814137
XXS NO	0 - 200 ppm	0.1 ppm	6811545
XXS NO <sub>2</sub>	0 - 50 ppm	0.1 ppm	6810884
XXS NO <sub>2</sub> LC	0 - 50 ppm	0.02 ppm	6812600
XXS SO <sub>2</sub>	0 - 100 ppm	0.1 ppm	6810885
XXS PH <sub>3</sub>	0 - 20 ppm	0.01 ppm	6810886
XXS PH <sub>3</sub> HC	0 - 2,000 ppm	1 ppm	6812020
XXS HCN	0 - 50 ppm	0.1 ppm	6810887
XXS HCN PC	0 - 50 ppm	0.5 ppm	6813165
XXS NH <sub>3</sub>	0 - 300 ppm	1 ppm	6810888
XXS CO <sub>2</sub>	0 - 5 Vol.-%	0.1 Vol.-%	6810889
XXS Cl <sub>2</sub>	0 - 20 ppm	0.05 ppm	6810890
XXS H <sub>2</sub>	0 - 2,000 ppm	5 ppm	6812370
XXS H <sub>2</sub> HC	0 - 4 Vol.-%	0.01 Vol.-%	6812025
XXS OV	0 - 200 ppm	0.5 ppm	6811530
XXS OV-A	0 - 200 ppm	1 ppm	6811535

# Ordering Information

XXS Amine	0 - 100 ppm	1 ppm	6812545
XXS Odorant	0 - 40 ppm	0.5 ppm	6812535
XXS COCl <sub>2</sub>	0 - 10 ppm	0.01ppm	6812005
XXS Ozone	0 - 10 ppm	0.01 ppm	6811540

ES = Energy saving

HC = High concentration

<sup>1</sup> Special calibrations possible for the Ex sensors (Standard: methane).

<sup>2</sup> Dräger provides a 3 year manufacturer's warranty on the Dräger X-am 5600 and these sensors. The legal rights arising from defects remain unaffected.

## Power supply units

NiMH power supply T42.0	3703887
Power pack & charging set consisting of: rechargeable NiMH power supply T42.0, charging module and a single charger (for worldwide use)	3703889
Battery holder ABT 0100 (without batteries)	8322237
Alkaline batteries T3 (2 pcs.) for battery holder 8322237	8322239

## Charging accessories

Charging module	8318639
Charging set basic, consisting of one charging module and a single power supply (worldwide use)	8320333
Power plug 100-240 VAC; 6.25 A, for charging up to 20 devices Adapter for power plug 8325736 is needed in addition.	8321850
Single charger (worldwide use) for max. 5 charger modules	8316994
Car charging connection cable 12 V / 24 V for a charging module	4530057
Vehicle charger mounting kit for one Dräger X-am 1/2/5x00 charging module	8318779
Charging adapter for charging a rechargeable battery without X-am device	8326101

## Pump accessories

Dräger X-am Pump (external pump)	8327100
Dräger X-am Pump incl. USB charger and shoulder strap	8327115
Hand pump adapter	8319195
CSE Set Dräger X-am Pump (incl. 5 m FKM hose)	8327117
Case for Dräger X-am Pump	8327104

# Ordering Information

## Calibration accessories

Calibration cradle	8318752
Dräger X-dock 5300 for Dräger X-am 1/2/5x00	8321880
Dräger Bump Test Station for Dräger X-am 5600, not including gas cylinder	8319131
Dräger Bump Test Station for Dräger X-am 5600, complete with one test gas cylinder 58L (gas and concentration variable)	8319130
Nonane Checker	8320080

## Communication accessories / software

Dräger GasVision license key	8325646 software: <a href="http://www.draeger.com/software">www.draeger.com/software</a> (free trial version)
Dräger CC-Vision	<a href="http://www.draeger.com/software">www.draeger.com/software</a>
USB DIRA with USB cable, communication adapter infrared to USB	8317409

## Area monitoring

Dräger X-zone 5500, 868 MHz, 24 Ah battery with diffusion cap	8324819
Dräger X-zone 5800 with integrated pump, 868 MHz, 24 Ah battery with diffusion and pump cap	8329030

In conjunction with the portable alarm amplifier Dräger X-zone 5500/5800, the devices are combined into system, e.g. to monitor entire work areas or to switch the alarm contact to external equipment.

Not all products, features, or services are for sale in all countries. Trademarks mentioned herein are the property of its respective owner. Trademarks may be owned by Drägerwerk AG & Co. KGaA (Dräger) or its affiliates in certain countries and not necessarily in the country in which this material is released. Visit [www.draeger.com/trademarks](http://www.draeger.com/trademarks) for the current status of Dräger's trademarks.

#### **Corporate Headquarters**

Drägerwerk AG & Co. KGaA  
Moislinger Allee 53–55  
23558 Lübeck, Germany  
■ [www.draeger.com](http://www.draeger.com)

#### **Region Europe**

Dräger Safety AG & Co. KGaA  
Revalstraße 1  
23560 Lübeck, Germany  
☎ +49 451 882 0  
☎ +49 451 882 2080  
✉ [info@draeger.com](mailto:info@draeger.com)

#### **Region Asia Pacific**

Draeger Singapore Pte. Ltd.  
61 Science Park Road  
The Galen #04-01  
Singapore 117525  
☎ +65 6872 9288  
☎ +65 6259 0398

#### **Region Middle East, Africa**

Dräger Safety AG & Co. KGaA  
Branch Office  
P.O. Box 505108  
Dubai, United Arab Emirates  
☎ +971 4 4294 600  
☎ +971 4 4294 699  
✉ [contactuae@draeger.com](mailto:contactuae@draeger.com)

#### **Region Central and South America**

Dräger Safety do Brasil Ltda.  
Al. Pucuruí, 51/61 – Tamboré  
06460-100 Barueri, São Paulo  
☎ +55 (11) 4689-4900  
✉ [relacionamento@draeger.com](mailto:relacionamento@draeger.com)



Locate your Regional Sales  
Representative at:  
[www.draeger.com/contact](http://www.draeger.com/contact)